

K 312 II



**K 312 II**

**NEW  
2011**

”

**Never miss THE MOMENT !**

”



SNIPER SCOPES



The red turret pops up when the elevating goes into the second turn

Optimized KAHLES AMV coatings realize nearly loss-free transmission in the critical spectral range of light (approx. 520 nanometers).

Magnifying reticle construction in first image focal plane for any shooting condition.




**K 312 II**

Parallax adjustment for highest precision


Easy-to-operate side adjustment and elevation adjustment.

Complex optical design with up to four objective lenses creates the unprecedented distortion-free image with an extremely wide, field-of-view

Subtension at 100 m / 100 yds



Mil 2



Reticle placement indicator



### Technical Specifications K 312 II

Magnification	3-12
Obj.lens diameter	50 mm (1.97 inch)
Field of view	35 - 10.5/ 100 yd
Eye Relief	90 mm (3.54 inch)
Diopter compensation	+2/-3.5 dpt
Parallax adjustment	30 m until endless
Impact pt. corr. per click	1 cm / 100 m
Elevation	2.4 m / 100 m (7.2 ft/100 yd)
Tube diameter	34 mm (1.34 inch)
Length	386 mm (15.2 inch)
Weight	800 g (28 oz)
Reticle	Mil 2
Parallax adj. marking	30 m until endless