

K 624 i



gegr. 1898  
AUSTRIA

**K 624 i**

**NEW  
2011**

”

**Never miss THE MOMENT !**

”



SNIPER SCOPES



Optimized KAHLES AMV coatings realize nearly loss-free transmission in the critical spectral range of light (approx. 520 nanometers).

Magnifying reticle construction in first image focal plane for any shooting condition.

A reticle placement indicator allows you to work in total darkness.

Parallax adjustment for highest precision

K 624 i

Light adjustment

Easy-to-operate side adjustment and elevation adjustment.

Complex optical design with up to four objective lenses creates the unprecedented distortion-free image with an extremely wide, field-of-view

Subtension at 100 m / 100 yds



Mil 3



Reticle placement indicator



### Technical Specifications K 624 i

Magnification	6-24
Obj.lens diameter	56 mm (2.2 inch)
Field of view	22.3 - 5.74 / 100 yd
Eye Relief	90 mm (3.54 inch)
Diopter compensation	+2/-3.5 dpt
Parallax adjustment	50 m until endless
Impact pt. corr. per click	1 cm / 100 m
Elevation	2.5 m / 100 m (7.5ft / 100 yd)
Tube diameter	34 mm (1.34 inch)
Length	405 mm (15.9 inch)
Weight	J50 g (33.6 oz)
Reticle	Mil 3 / 4 illuminated
Parallax adj. marking	50 m until endless