

Press release

Guntramsdorf, June 2023



NEW K18i-2

THE MATCH WINNER – WITH 50-METER FIELD OF VIEW



The very successful K18i has been further enhanced with the support of pro shooters and optimised for even faster target acquisition. The resulting 50-m/100-m field of view of the new K18i-2 is now setting the new standard for IPSC and 3-Gun matches.

The new K18i-2 offers the expected excellent imaging as well as a particularly user-friendly eyepiece, which allows quick and easy focusing and immerses you in an image that stays sharp right to the edges. The true 1.0x magnification, the fine and extra-bright day/night illuminated reticle in 2nd focal plane combined with the innovative "MAX LIGHT" reticle illumination function for extreme backlight situations and the 8x magnification allow ultra-fast target acquisition at close and medium distances.

Along with other relevant features, the two individually adjustable throw levers included and the robust 34mm Ø main tube support maximum performance.

The new K18i-2 presents an uncompromising combination of an unparalleled field of view and outstanding optical performance, making it the perfect choice for competitions decided on tenths of a second.

The K18i-2 will be available for £ 2490 from specialist retailers from September 2023.

Josef Kampfer, Head of Public Relations

KAHLES Gesellschaft m.b.H

Danfoss-Straße 5, 2353 Guntramsdorf | Austria | +43 (0) 664 2353504 | j.kampfer@kahles.at | kahles.at

Press release

Guntramsdorf, June 2023



KAHLES

PRODUCT HIGHLIGHTS

- ◆ Unparalleled 50-m field of view
- ◆ 8x zoom and true 1.0x magnification
- ◆ 2 sizes of integrated throw lever with freely selectable position
- ◆ Extra-bright day/night illuminated reticle in 2nd focal plane with MAX LIGHT function
- ◆ 3GR reticle designed with pro shooters especially for IPSC and 3-Gun

TECHNICAL DATA

K18i-2	1-8x24i
Magnification	1-8
Objective lens diameter (mm)	24
Eye relief (mm)	95
Field of view (m/100m)	50.0–6.2
Diopter compensation (dpt)	+2/-3
Exit pupil diameter (mm)	8.0–2.97
Twilight factor (DIN 58388)	2.9–13.9
Parallax-free (m)	100
Impact correction per click (mm/100 m)	10
Adjustment range E/W (m/100 m)	2.0/2.0
Tube diameter (mm)	34
Objective filter thread	M30 x 0.75
Length (mm)	300
Weight (g)	640
Reticle	3GR
Focal plane	2
Illuminated, MAX LIGHT function	✓
Battery type	CR2032
Warranty (years)	10 (2 for electronics)
Accessories (optional)	Flip-up cover for objective lens/eyepiece K Ballistic Turret (BT)

High-resolution images are available in the [newsroom](#) on our website.

Josef Kampfer, Head of Public Relations

KAHLES Gesellschaft m.b.H

Danfoss-Straße 5, 2353 Guntramsdorf | Austria | +43 (0) 664 2353504 | j.kampfer@kahles.at | kahles.at