

K525i (left side windage)

PROFESSIONAL CHOICE FOR HIGHEST DEMANDS



The K525i combines maximum optical performance and precision with unique handling and ergonomics. A rugged riflescope for professionals, with windage optional left or right, precise illuminated reticles in 1st focal plane and the unique TWIST GUARD windage.

PRODUCT HIGHLIGHTS

- Maximum optical performance – field of view, high contrast image, high definition
- Absolutely reliable repeat accuracy and precise, clearly defined click mechanism
- Optional left or right side windage
- Parallax wheel integrated into the elevation turret (patented) (20 m to ∞)
- Innovative TWIST GUARD windage (patented)
- Precise illuminated reticle in 1st focal plane

TECHNICAL DATA

Magnification:	5 - 25
Eye relief:	3.74 in
Field of view:	21.3 - 4.5 in/100 yds
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	16.7 - 37.4
Impact correction per click:	.1 MRAD ¼ MOA
Adjustment range (E/W):	104.4 / 46.8 in/100 yds 29.0 / 13.0 MILS 100.0 / 45.0 MOA
Parallax adjustment:	20 m till ∞
Tube diameter:	34 mm / 1.34 in
Length:	14.8 in
Weight:	34.2 oz
Illuminated:	Yes
Warranty:	10 years

FEATURES



1st focal plane



Main tube 34 mm



Adjustment direction CCW



MOA or MIL



Windage left or right




Zero Stop




TWIST GUARD windage


RETICLES / SUBTENSIONS




AMR




MOAK



MSR2/Ki



SKMR



SKMR4