

## K525i (right side windage)

PROFESSIONAL CHOICE FOR HIGHEST DEMANDS



The K525i combines maximum optical performance and precision with unique handling and ergonomics. A rugged riflescope for professionals, with windage optional left or right, precise illuminated reticles in 1 st focal plane and the unique TWIST GUARD windage.

## PRODUCT HIGHLIGHTS

- Maximum optical performance – field of view, high contrast image, high definition
- Absolutely reliable repeat accuracy and precise, clearly defined click mechanism
- Optional left or right side windage
- Parallax wheel integrated into the elevation turret (patented) (20 m to  $\infty$ )
- Innovative TWIST GUARD windage (patented)
- Precise illuminated reticle in 1 st focal plane

## TECHNICAL DATA

Magnification:	5 - 25
Objective lens diameter:	56 mm
Exit pupil:	9.5 - 2.3 mm
Eye relief:	95 mm
Field of view:	7.1 - 1.5 m/100 m
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	16.7 - 37.4
Impact correction per click:	.1 MRAD   ¼ MOA
Adjustment range (E/W):	2.9 / 1.3 m/100 m
Parallax adjustment:	20 m till ∞
Tube diameter:	34 mm
Length:	377 mm
Weight:	970 g
Illuminated:	Yes
Warranty:	10 years

## FEATURES



1st focal plane



Main tube 34 mm



Adjustment direction CW  
or CCW



MOA or MIL



Windage right




Zero Stop




TWIST GUARD windage


## RETICLES / SUBTENSIONS




AMR




MSR2/Ki




Mil4+




SKMR4



SKMR



TREMOR 3



MOAK