

## K318i (windage right)

### ULTRASHORT PRECISION TOOL



The K318i means optical and mechanical perfection packed into an ultrashort design. With precise illuminated reticles in 1 st focal plane, sharply defined throughout the entire magnification range and the unique TWIST GUARD windage.

### PRODUCT HIGHLIGHTS

- Ultrashort and lightweight riflescope with wide field of view and high contrast image
- Absolutely reliable repeat accuracy and precise, clearly defined click mechanism
- Optional left or right side windage
- Innovative TWIST GUARD windage (patented)
- Parallax wheel integrated into the elevation turret (patented) (25 m to  $\infty$ )
- Precise illuminated reticles in 1 st focal plane

## TECHNICAL DATA

Magnification:	3.5 - 18
Objective lens diameter:	50 mm
Exit pupil:	6.9 - 2.8 mm
Eye relief:	92 mm
Field of view:	9.3 - 2.0 m/100 m
Diopter compensation:	+2.5 / -3.5 dpt
Twilight factor (DIN 58388):	13.2 - 30.0
Impact correction per click:	.1 MRAD   ¼ MOA
Adjustment range (E/W):	3.0 / 1.5 m/100 m
Parallax adjustment:	25 m till ∞
Tube diameter:	34 mm
Length:	313 mm
Weight:	940 g
Focal plane:	1
Illuminated:	Yes
Warranty:	10 years

FEATURES



1st focal plane




Main tube 34 mm



Adjustment direction CW  
or CCW



MOA or MIL



Windage left or right




Zero Stop




TWIST GUARD windage


RETICLES / SUBTENSIONS



MSR/Ki



SKMR3



MOAK