

# K525i DLR (right side windage)

DYNAMIC LONG RANGE



K A H L E S



The K525i combines maximum optical performance and precision with unique handling and ergonomics. The DLR variant is optimised for the fast action nature of Dynamic Long Range competitions. It features extended field of view, easy to read clicks, extralong throw lever and parallax spinner.

## PRODUCT HIGHLIGHTS

- Maximum optical performance with extra wide field of view
- 100 clicks per rotation - absolutely reliable repeat accuracy and clearly defined clicks
- Extra-large turret lettering for easy and fast reading
- Optional left or right TWIST GUARD windage
- Special equipment: extralong throw lever & parallax spinner for quick adjustments
- Precise illuminated SKMR4 reticle in 1st focal plane

## TECHNICAL DATA

Magnification:	5 - 25
Objective lens diameter:	56 mm
Exit pupil:	9,5 - 2,3 mm
Eye relief:	95 mm
Field of view:	7.7 - 1.6 m/100 m
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	16.7 - 37.4
Impact correction per click:	0,1 MRAD
Adjustment range (E/W):	2,9/1,3
Parallax adjustment:	20-∞
Tube diameter:	34 mm
Length:	377 mm
Weight:	995 g
Focal plane:	1
Illuminated:	Yes
Warranty:	10 years (2 years electronic)

## FEATURES




1st focal plane



Main tube 34 mm



Adjustment direction CCW



Windage right




Zero Stop




TWIST GUARD windage EasyRead elevation turret

## RETICLES / SUBTENSIONS



SKMR4



SKMR