

K3 18i (windage left)

ULTRASHORT PRECISION TOOL



The K3 18i means optical and mechanical perfection packed into an ultrashort design. With precise illuminated reticles in 1st focal plane, sharply defined throughout the entire magnification range and the unique TWIST GUARD windage.

PRODUCT HIGHLIGHTS

- Ultrashort and lightweight riflescope with wide field of view and high contrast image
- Absolutely reliable repeat accuracy and precise, clearly defined click mechanism
- Optional left or right side windage
- Innovative TWIST GUARD windage (patented)
- Parallax wheel integrated into the elevation turret (patented) (25 m to ∞)
- Precise illuminated reticles in 1st focal plane

TECHNICAL DATA

Magnification:	3.5 - 18
Objective lens diameter:	50 mm
Exit pupil:	6.9 - 2.8 mm
Eye relief:	92 mm
Field of view:	9.3 - 2.0 m/100 m
Diopter compensation:	+2.5 / -3.5 dpt
Twilight factor (DIN 58388):	13.2 - 30.0
Impact correction per click:	.1 MRAD ¼ MOA
Adjustment range (E/W):	3.0 / 1.5 m/100 m
Parallax adjustment:	25 m till ∞
Tube diameter:	34 mm
Length:	313 mm
Weight:	940 g
Focal plane:	1
Illuminated:	Yes
Warranty:	10 years

FEATURES



1st focal plane



Main tube 34 mm



Adjustment direction CW
or CCW



Zero Stop



TWIST GUARD windage




Windage left or right




MOA or MIL


RETICLES / SUBTENSIONS




MSR/Ki



SKMR3



TREMOR 3



MOAK