

**NEW KAHLES K525i**

Professional choice for highest demands



The big brother of ultrashort K318i is the new flagship of KAHLES in the field of tactical riflescopes. It combines in an inimitable way maximum optical performance and highest precision with unique handling and ergonomics. A perfect package for the highest demands.

The rugged K525i with its practical magnification range has been developed for tactical use and long distances. It is intended to help ambitious shooters to achieve records. The clearly defined, precise clicks, together with the exceptional repeat accuracy, provide highest precision and reliability.

Due to the unique KAHLES arrangement, all operating elements can easily and comfortably be operated with the intuitively preferred hand, without having to reach over the scope and without having to move out of the shooting position. The patented central arrangement on top of the riflescope makes right- and left-handed operation equally comfortable. Ergonomically the windage is ideally placed on the left side for right-handed shooters and on the right side for left-hand shooters.

The essential information on the turrets is clearly readable from the aiming position. The large adjustment range provides enough reserve for each situation. Consequently, at competitions, the shooter can fully concentrate on the essential.

The K525i is available with 5 precise illuminated reticles in first focal plane. Beside the proven and popular SKMR3, SKMR and MOAK, there are two further developments with the MSR2/Ki and the Mil4+.

Josef Kampfer,  
Head of Public Relations

KAHLES Gesellschaft m.b.H  
Danfoss-Straße 5, 2353 Guntramsdorf | Austria | T: +43/2236/520 20/36 | E: j.kampfer@kahles.at | kahles.at

## Press release

Guntramsdorf, March 2018



The innovative, patented TWIST GUARD windage with its freely rotating end cover, reliably prevents an accidental movement of the windage. This simple solution does not only protect the windage from accidental movement, it also allows the shooter a fast and unhindered handling of the windage without cumbersome need of “locking” and “unlocking”.

The allen key for zeroing the turrets, numbers to those little, practical details. It is housed in the cap of the illumination unit and therefore always available. Hence the illumination unit can easily be opened without any tool.

The K525i is available as of August 2018 at retailers for € 3,300.

### PRODUCT HIGHLIGHTS

- .: Maximum optical performance-field of vision, contrast and picture quality
- .: Exceptional repeat accuracy
- .: Precise and clearly defined click mechanism 0.1 MIL, MRAD or ¼ MOA
- .: Side adjustment left or right
- .: Parallax wheel integrated in the elevation turret (patented) 20m - ∞
- .: Innovative, patented TWIST GUARD windage
- .: Precise illuminated reticles in first focal plane – SKMR3, SKMR, MSR2, Mil4+, MOAK
- .: Large adjustment range with 2.9m (E) and 1.3m (W) at 100m
- .: Zero Stop

### Picture material:

High resolution images can be found on our website in the [Newsroom](#).

### KAHLES – since 1898

In the course of its 120 years company history KAHLES has set many milestones. Today we develop and produce at our facility in Guntramsdorf near Vienna, far-optical precision devices at highest technical standards for ambitious shooters and hunters. We do that with uncompromised focus on the real essential, based on profound user insight and a wealth of know-how.

Josef Kampfer,  
Head of Public Relations

KAHLES Gesellschaft m.b.H

Danfoss-Straße 5, 2353 Guntramsdorf | Austria | T: +43/2236/520 20/36 | E: j.kampfer@kahles.at | kahles.at

## Press release

Guntramsdorf, March 2018



KAHLES

		<b>K525i 5-25x56i</b>
Magnification		5 – 25
Objective lens diameter	(mm)	56
Exit pupil diameter	(mm)	9.5 – 2.3
Eye relief	(mm)	95
Field of View	(m/100m) (ft/100yds)	7.1 – 1.5 21.7 – 4.4
Diopter compensation	(dpt)	-3.5 to 2.0
Impact correction/click (MIL/100m / MOA)		0.1 / ¼
Adjustment range E/W	(m/100m) (ft/100 yds)	2.9 / 1.3 8.6 / 3.9
Parallax adjustment	(m) (yds)	20 - ∞ 22 - ∞
Objective filter thread		M58 x 0.75
Length	(mm) (in)	377 14.8
Weight	(g) (oz)	970 34.2
Tube diameter	(mm)	34
Reticle 1. focal plane		SKMR3 / SKMR / MSR2 / Mil4+ / MOAK
Illuminated		yes
Adjustment direction		cw/ccw,
Windage		Left or Right
Accessories		sunshield; flip Ups; killflash

Josef Kampfer,  
Head of Public Relations

KAHLES Gesellschaft m.b.H

Danfoss-Straße 5, 2353 Guntramsdorf | Austria | T: +43/2236/520 20/36 | E: j.kampfer@kahles.at | kahles.at