

K1050i FT

FIELD TARGET FOR PERFECTIONISTS



K A H L E S



The K1050i FT offers a uniquely precise experience. With the special parallax focus ranging from 9 to 66 yards (8 to 60 metres) and an illuminated reticle in the 2nd focal plane, it has been optimally designed for Field Target competitions.

Special Order

PRODUCT HIGHLIGHTS

- Developed together with professionals for highest precision in Field Target competitions
- Perfect image quality, even at 50 x magnification
- Parallax wheel integrated into the elevation turret (patented) 8 – 60 m
- Illuminated reticle with fine structure for maximum precision
- Also available with silver coating

TECHNICAL DATA

Magnification:	10 - 50
Eye relief:	3.74 in
Field of view:	8.7 - 1.8 in/100 yds
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	23.6 - 52.9
Impact correction per click:	MOA
Adjustment range (E/W):	57.6/43.2 in/100 yds 16.0/12.0 MILS 55.0/41.3 MOA
Parallax adjustment:	8 - 60 m
Tube diameter:	30 mm / 1.18 in
Length:	16.9 in
Weight:	36.7 incl. parallax wheel (4.9) oz
Focal plane:	2
Illuminated:	Yes
Warranty:	10 years

FEATURES



2nd focal plane




Main tube 30 mm



Adjustment direction CCW




MOA



Windage right

RETICLES / SUBTENSIONS



MHR