

K525i DLR (right side windage)

DYNAMIC LONG RANGE



The K525i combines maximum optical performance and precision with unique handling and ergonomics. The DLR variant is optimized for the fast action nature of Dynamic Long Range competitions. It features extended field of view, easy to read clicks, extralong throw lever and parallax spinner.

PRODUCT HIGHLIGHTS

- Maximum optical performance with extra wide field of view
- 100 clicks per rotation - absolutely reliable repeat accuracy and clearly defined clicks
- Extra-large turret lettering for easy and fast reading
- Optional left or right TWIST GUARD windage
- Special equipment: extralong throw lever & parallax spinner for quick adjustments
- Precise illuminated SKMR4 reticle in 1st focal plane

TECHNICAL DATA

Magnification:	5 - 25
Objective lens diameter:	2,20 in
Eye relief:	3.74 in
Field of view:	25.2 - 5.2 in/100 yds
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	16.7 - 37.4
Impact correction per click:	0,1 MRAD
Adjustment range (E/W):	2,9/1,3 m/100m
Parallax adjustment:	20-∞
Tube diameter:	1,33 in
Length:	14.8 in
Weight:	35.0 oz
Focal plane:	1
Illuminated:	Yes
Warranty:	10 Years

FEATURES




1st focal plane



Main tube 34 mm



Adjustment direction CCW



Windage right




Zero Stop



TWIST GUARD windage EasyRead elevation turret

RETICLES / SUBTENSIONS



SKMR4