

# K624i

PROFESSIONAL CHOICE FOR LONG DISTANCES



The K624i sets standards in handling and ergonomics thanks to the unique arrangement of its operating elements. It offers outstanding optical performance, mechanical perfection and a unique range of well proven reticles for professionals.

## PRODUCT HIGHLIGHTS

- Wide field of view, exceptionally comfortable eyepiece and high contrast image
- Precise, clearly defined click mechanism and reliable repeat accuracy
- Optional left or right side windage
- Parallax wheel integrated into the elevation turret (patented) (50 m to  $\infty$ )
- Precise illuminated reticles in 1<sup>st</sup> focal plane

## TECHNICAL DATA

Magnification:	6 - 24
Eye relief:	3.54 in
Field of view:	20.4 - 5.1 in/100 yds
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	18.3 - 36.7
Impact correction per click:	.1 MRAD   ¼ MOA
Adjustment range (E/W):	90.0 / 39.6 in/100 yds   25.5 / 11.25 MILS   86.0 / 37.8 MOA
Parallax adjustment:	50 m till ∞
Tube diameter:	34 mm / 1.34 in
Length:	15.9 in
Weight:	33.5 oz
Focal plane:	1
Illuminated:	Yes
Warranty:	10 years

## FEATURES



1st focal plane



Main tube 34 mm



Adjustment direction CCW



MIL




Windage left or right



Zero Stop

## RETICLES / SUBTENSIONS



SKMR4